

Technical data sheet

Aduro Vetrofix V

8133 000210

Retardant for the glass coating using a paint roller for **industrial and professional use**

PRODUCT DESCRIPTION

General

Special mixture of solvents to optimize the processability of the mixture Aduro Vetrocolor and ADLER Vetro PUR-Härter due to retarded drying, if glass elements have to be coated by paint roller.

Application area




- As addition to Aduro Vetrocolor for coating glass elements.
- The product does not influence the surface quality of the coating system (chemical and mechanical resistance).
- Suitable for humid areas.

PROCESSING

Instructions for use

- Aduro Vetrofix V must be incorporated carefully into the hardened varnish by stirring.
- Use a paint roller for application (short haired roller – see supplementary products).
- Please follow our „**Guidelines for glass coating with polyurethane paints for humid areas**“. Mixed varnish can be used as described in the relative technical data sheet.

Quantity to be added



10 - 20 %

Mixing ratio:


- 100 percent by weight of Aduro Vetrocolor in the desired colour shade
- + 20 percent by weight of ADLER Vetro PUR-Härter
- + 10-20 percent by weight of Aduro Vetrofix V 8133 000210

Pot life of the mixing

8 hours



Cleaning the working equipment



With ADLER DD-Verdünnung (thinner) 80019 or ADLER Waschverdünnung 80077.

ORDERING INFORMATION

Size of trading unit


400 g

Supplementary products

Aduro Vetrocolor 2495
ADLER Vetro PUR-Härter 8232 000210
ADLER DD-Verdünnung 80019
ADLER Waschverdünnung 80077
Lackroller WL 10 cm 9645 811
Lackroller WL 25 cm 9646 011

FURTHER DETAILS


Durability / storage



At least 1 year in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Safety-related information



Please follow the associated safety data sheet, the latest version can be retrieved from the Internet at www.adler-lacke.com.

The product is only suitable for the industrial and professional use