

Technical data sheet

ADLER Silberlack (*silver paint*)

54814



10 % 80367

Product description

Weather-proof, thixotrope, metallic satin-finished special-effect paint on alkyd resin basis with rust protection, heat-resistant up to approx. 150°C.

Fields of application

On metal and wood for indoor and outdoor application.

Application

Coating, rolling, spraying

Spraying is only permitted in spray booths subject to the VOC Directive.

Surface pre-treatment

The surface must be non-crackling, clean and grease-free.

Old coats

Remove loose coats. Slightly sand bonded coats and verify whether they are compatible with ADLER Silberlack (*silver paint*). If necessary, strip the entire old coat.

Metal

Steel: The metal parts must be clean, grease-free and dry.
Zinc, aluminium: For adhesiveness, apply ADLER Unigrund and/or ADLER 2K Expxi-Grund (*2-component epoxy primer*)

Wood

For exterior surfaces, first apply Pullex-Imprägniergrund (*impregnation primer*)

Topcoat

ADLER Silberlack (*silver paint*) 2x

Thinner

Do not thin if you use brushes or rollers.
For spraying, thin with approx. 10 % ADLER KH-Spritzverdünnung (*synthetic spray thinner*).

Application and object temperature

At least + 5 °C

Drying time

(room temperature 20°C)
(100 µm wet coat)

Completely dry 2 hours
Repaintable after 8 - 10 hours

Strong coat thickness, low temperatures and/or high humidity may result in a significantly longer drying time.

Working equipment

Clean with ADLER KH-Spritzverdünnung (*synthetic spray thinner*).

Spreading rate

Approx. 10 m²/l

03-07 (replaces 02-07)

ADLER-Werk Lackfabrik, A-6130 Schwaz, 05242/6922-450

Continued

ADLER Silberlack (silver paint) 54814

Packaging	375 ml, 750 ml
Colour	Silver 54814 (ca. RAL 9006)
Storage	Dry and frost-protected Please shut open containers well and upend them.
Safety information	Please pay attention to the safety information sheet!

PACHE SARL